

Features:

- Universal output voltage adjusted to latest router models (selectable by switch)
- 0ms transfer time
- Compact size
- 230Vac input voltage – wide range
- USB socket for mobile devices charging
- „Cold start” – switch on without mains supply
- Can work in power bank mode
- Automatic charging
- PoE (RouterUPS-15-PoE version)



Example applications:

		
<p>Routers WIFI</p>	<p>Switch</p>	<p>IP cameras</p>







Technical parameters:

MODEL	RouterUPS-15	RouterUPS-15-POE	RouterUPS-30	RouterUPS-30-POE
Output power	15W	15W	30W	30W
INPUT				
Input voltage	Rated: 230VAC Input voltage range: 100Vac – 240Vac			
Input frequency	50/60Hz ± 10% (auto-selection)			
Supply wire	II class			
OUTPUT				
Output voltage	5V/3A max And one to be selected: 9V/1,33A max 12V/1,25A max	One to be selected: 9V/1,33A max 12V/1,25A max One to be selected PoE: 15V/1A max 24V/0,62A max	5V/3 max And one to be selected: 9V/2A max 12V/2A max	One to be selected: 9V/2A max 12V/2A max One to be selected PoE: 15V/1A max 24V/1A max
Output sockets	2	2	2	2
Socket type	2,1x5,5mm	2,1x5,5mm (1pc) RJ24 (1 pair)	2,1x5,5mm	2,1x5,5mm (1pc) RJ24 (1 pair)
Overall output power	15W	15W	30W	30W
USB socket	5V/1A	5V/1A	5V/2A	5V/2A
BATTERY				
Type	Lithium-ion			
Capacity	8800mAh			
OTHER				
Dimensions (L x W x H)	159 x 104 x 28 mm			
Weight	0,4 kg			
Reset button	No	Yes	No	Yes
Humidity	20~90% RH @ 0~40°C (non-condensating)			
Case color	black			
Front panel indicator				
STATUS	Continued GREEN – mains AC power mode Continued RED – battery mode			
9V / 12V	Continued GREEN – indicates output voltage selection			
Battery 25%-100%	4-point battery capacity indicator			

Standard accessories:

- internal battery
- supply wire
- manual

MODEL	RouterUPS-15	RouterUPS-15-POE	RouterUPS-30	RouterUPS-30-POE
EAN				

MODEL	RouterUPS-15 / RouterUPS-30	RouterUPS-15-POE / RouterUPS-30-POE
Rear panel	