


CABLE DESIGN

UTPCat.5E LSZH VIOLET (Solid)

P/N 65504AH



CONSTRUCTION			
1 - CONDUCTOR	Annealed copper wire	diameter	0.495±0.01 mm
2 - INSULATION	Solid polyethylene	diameter	1.03±0.02 mm
3 - PAIRS	Color code :		blue / white-blue, orange / white-orange green / white-green, brown /white-brown
4 - NOT USE			
5 - OUTER JACKET	LSZH compound (Violet RAL4005)	thickness diameter	0.47 mm Minimum
		External diameter	6.3±0.3 mm
6 - MARKING	LEXI NET 65504AH 4PR 24AWG UTP SOLID LSZH CABLE ETL VERIFIED TIA/EIA-568-B.2 CAT.5e.. <i>metric m (ww/yy)</i>		

ELECTRICAL CHARACTERISTICS									
<ul style="list-style-type: none"> ● Mutual Capacitance(maximum) : 5.6 nf/100M ● Capacitance Unbalance(maximum) : 330 pF ● Velocity of Propagation : 68 % ● Delay Skew : 45 ns/100m 									
FREQUENCY (MHz)	ATTENUATION dB/100m MAX	NEXT dB min	PS-NEXT dB MIN	RL dB MIN	ELFEXT dB MIN	PS-ELFEXT dB MIN	IMPEDANCE (OHMS)	WP-ACR (dB/100m) MIN	PS-ACR dB/100m MIN
1	—	65.3	62.3	20.0	63.8	60.7	100±15	63.3	60.3
4	4.1	56.3	53.3	23.0	51.7	48.7	100±15	52.2	49.2
10	6.5	50.3	47.3	25.0	43.8	40.7	100±15	43.8	40.8
16	8.2	47.3	44.2	25.0	39.7	36.7	100±15	39.1	36.0
20	9.3	45.8	42.8	25.0	37.7	34.7	100±15	36.5	33.5
25	10.4	44.3	41.3	24.3	35.8	32.8	100±15	33.9	30.9
31.25	11.7	42.9	39.9	23.6	33.9	30.8	100±15	31.2	28.2
62.5	17.0	38.4	35.4	21.5	27.8	24.8	100±15	21.4	18.4
100	22.0	35.3	32.3	20.1	23.8	20.7	100±15	13.3	10.3
ELECTRICAL STANDARD ACCORDING TO TIA/EIA 568-B.2									