



## EtherHaul™-5500FD Datasheet



Siklu

# 5Gbps 70/80GHz radio – High Bandwidth for Demanding Networks

The EH-5500FD brings 5Gbps full duplex throughput for high capacity applications with fiber-like layer-1 transparency

## Applications for a Wide Range of Vertical Markets

- Business Broadband
- Campus Connectivity
- GTTH – Gigabit To The Home

## Robust & Futureproof

The EH-5500FD radio delivers 5Gbps full duplex point-to-point wireless Ethernet connectivity to futureproof your network. Operating over the interference-free 71-76/81-86GHz band, the FDD EH-5500FD has additional output power and wider channels, making it easy for providers and enterprises to extend their networks by very quickly adding affordable, high capacity wireless links that are easy to install and maintain.

## Carrier Grade Performance over Wireless

The EH-5500FD incorporates adaptive bandwidth coding and modulation for high availability and, a dual power feed PoE+/direct DC for increased redundancy.

## Fiber-Like Performance

The EH-5500FD provides transparent layer 1 connectivity and easily integrates with Ethernet switches or MPLS routers to enable deployment in ring, mesh or any high resiliency topology.

## Small Size, Easy to Deploy & Manage

The all-outdoor radio has a small footprint that alleviates site acquisition. Its light-weight and small size make for a quick and easy installation, while the intuitive web GUI manages local and remote units to enable fast commissioning and configuration. Three antenna options enable street-level deployment and meet varying distance and availability requirements.

## Based on Siklu's Field Proven Platform

The EH-5500FD is the high-capacity 5Gbps evolution of the best-selling EtherHaul™ series - the world's most deployed millimeter wave radio. Tens of thousands of links have been deployed and are performing reliably in diverse weather conditions all over the globe.

## Fast Spectrum Acquisition at Affordable Cost

The E-band spectrum is uncongested, even in rural or dense urban areas. Using a high-gain pencil-beam antenna, guarantees available spectrum anywhere and maximizes spectrum re-use. Additionally, the E-band spectrum offers low licensing fees and quick licensing processes.

## Exceptional Value

The EH-5500FD provides fast return on investment (ROI) and minimizes total cost of ownership (TCO). The advanced 5Gbps system delivers an unbeatable price per MB. Its small and light form factor lowers installation costs, increases reliability and reduces site visits. Ultra-fast activation time with the unbeatable reliability will become your 'winning card' in any competitive environment.

The EH-5500FD is available with multi-step licenses for scalable rollouts.



# EtherHaul™-5500FD Specifications



Frequency	71-76GHz / 81-86GHz, FDD
Antenna options	0.5ft. (16 cm) - 38dBi antenna gain 1ft. (31cm) – 43dBi antenna gain 2ft. (65cm) – 50dBi antenna gain
Reach	Typical: 1 mile; Maximum: 1.5 miles (rain zone-dependent)
Modulation & Adaptive rate	BPSK-1/BPSK-2/QPSK-1/QAM16/QAM32 adaptive bandwidth, coding and modulation - boost gain by up to 25 dB
Channels	User selectable, 3x 1250MHz wide, non-overlapping
Throughput	2000Mbps, license-key upgradeable to 5000Mbps
Link budget (BER=10 <sup>-6</sup> )	147dB / 157dB / 171dB (incl. 0.5ft. / 1ft. / 2ft. antenna gain)
Interfaces	1x 10GE port SFP+, 1x copper RJ45 for management only
Power	45W PoE-in via management port and/or 36 ÷ 57VDC (flexible grounding) direct DC
Management & provisioning	Out-of-band local management & over-the-air remote management, Web GUI (one-click configuration of local and remote units), Embedded CLI SNMPv2/3, TACACS+, RADIUS Zero-touch turn up
Topologies	Ring, daisy-chain, mesh
Conformance	FCC CFR Part 101 & ETSI EN 302 217-2-2; EMC: USA FCC 47CFR.part 15 & ETSI EN 301 489; Safety UL/EN 60950
Environmental	Operating Temperature: -45° to +55°C (-49° to +131°F) Ingress Protection Rating: IP67
Dimensions	ODU + 0.5ft antenna: 9.17" x 8.11" x 5.55" (23.3cm x 20.6cm x 14.1cm) ODU + 1ft antenna (Dia. x Depth): 31cm x 13cm (12.2" x 4.3") ODU + 2ft antenna (Dia. x Depth): 65cm x 37cm (25.6" x 15.35")
Weight	ODU + 0.5ft antenna: 9.2lbs. (4.2kg) ODU + 1ft. antenna: 9.9lbs. (4.5kg) ODU + 2ft. antenna: 24.3lbs (11kg)

REV B0